

SURFACE MOUNTED "AR2 FRAME "



- Traditional square shape.
- Lighting distribution:
 - Downward light from the punched optical diffuser.
 - Spill luminance via the frame reflector.
- Normal (or electronic) ballast.

LAMPS

T8 fluorescent lamps : 18 w , 36 w.

Compact fluorescent lamps : 11w,18w, 36w , 55 w .

Light controllers :




- Punched metallic parabolic optical diffuser for lamp screening, down the frame sides.
- Curved frame reflector, producing indirect lighting.

Frame reflector material :

"S" : Anodized matted "satin" aluminum reflector.

"P" : Steel sheet painted electro statically, white color.

LUMINAIRE TYPES & DIMENSIONS



| LUMINAIRE TYPE | LAMP (S) | DIMENSIONS | |
|----------------|------------|------------|----|
| | | AxB | C |
| 1 18 SM AR2 | 1x18w T8 | 635 | 95 |
| 2 18 SM AR2 | 2x18w T8 | 635 | 95 |
| 1 36 SM AR2 | 1x36w T8 | 1235 | 95 |
| 2 36 SM AR2 | 2x36w T8 | 1235 | 95 |
| 1 11 SM AR2 | 1x11w CFL | 300 | 95 |
| 1 18 SM AR2 | 1x18w CFL | 500 | 95 |
| 1 36 SM AR2 | 1x36w CFL | 500 | 95 |
| 1 55 SM AR2* | 1x55w CFL | 605 | 95 |

(add reflector material to the luminaire type).

T8 : Ø 26 mm traditional tubular fluorescent lamps.

CFL : compact fluorescent lamps.

"*" : Unit with electronic ballast only.